Ceiling Access Hatch



Air-tight type that is superior to corrosion.



Detail drawing Hanger Inner frame board min.85mm ~ max.138mm material (separate) Air-tight material Board holder Thickness: min. 3mm, max. 35mm ۲ 45 Outer frame Inner Frame 9.5 22.5 Opening dimensions Outer frame dimensions

Wood framing detail drawing



Material specifications

Parts	Materials	Finish			
Inner • Outer Frame	SUS304	HL (Flame Part)			
Lock	SUS304	-			
Support bracket	SUS304	-			
Hinge unit	SUS304	-			
Board holder	SUS304	_			
Air-tight material	EPDM	-			
Hanger	SUS304	-			

Model	Size C	Outer frame dim. (mm)	Opening dim. (mm)	Inner Frame Board Cutting size (mm)	Name	Unit	Qty per Carton	Accessories(pcs)
								Hanger
CDS	45	465.4	454	412	CDS45	- 1	5	4
CDS	60	617.4	606	564	CDS60		3	4

•Installable on wood. (Screws not included)

⚠

 The CDS ceiling access hatch improves HVAC efficiency but is not fully airtight. Stainless steel is generally rust-resistant but can stain or corrode depending on conditions. Even corrosion-resistant CDS hatch may corrode quickly in pools or sulfur-rich hot springs.
--