

CKR-2

| Depth (mm) | Width (mm) | | | | | | | | | |
|------------|------------|-----|------|------|------|------|------|------|------|------|
| | 600 | 900 | 1000 | 1200 | 1300 | 1350 | 1500 | 1650 | 1800 | 1950 |
| 400 | | | | | | | | | | |
| 500 | | | | | | | | | | |
| 520 | | | | | | | | | | |
| 600 | | | ● | | ● | | | ● | | ● |
| 650 | | | | | | | | | | |
| 750 | | | ● | | ● | | | ● | | ● |
| 900 | | | ● | | ● | | | ● | | ● |

| | | | | |
|-----------------------------------|-----------------|---------|---------------|-----------------------|
| Handle height (from ground level) | Material | Size | Assembly Type | Anchor bolts included |
| 760mm | Stainless Steel | 11 type | | |

Designed with safety and ease of use in mind.

Features

- Space-efficient rotary top door for easy operation.
- Standard-equipped high-durability rotary dampers. (One on each side)
- Internal level adjustment for easy installation. (0–40 mm adjustment range)
- Ideal for small residential complexes and commercial facilities.

POINT 1

Quiet door operation


Door opening and closing noise is reduced by approximately 25% with the use of rotary dampers.

Durability of rotary dampers

Passed a 100,000-cycle opening and closing test!

* Assuming the rotary door is opened and closed 8 times per week per household, this corresponds to **approximately 20 years** of use.

* This does not guarantee the service life. Durability may vary depending on actual usage conditions and frequency of use.



Optional Accessories



* (Optional accessories are sold separately.)

POINT 2



Space-saving door

The upper door is a rotary-type door for easy operation.

It rotates and stores inside the unit, enabling effective use of the upper space.

The front door uses a proprietary vertical sliding mechanism that allows opening and closing even in locations with no front clearance.

POINT 3

Designed with a safety clearance to help prevent fingers from being caught.



Padlock Compatible

The latch is equipped with a temporary locking function and can be fitted with a commercially available padlock. This helps prevent unauthorized waste disposal on non-collection days and deters tampering. *(Padlock not included.)

- Use DAIKEN padlocks DPR-125 (Φ4 mm shackle), DPR-130 (Φ5 mm shackle), or DPR-140 (Φ6.4 mm shackle).

POINT 4

Prevents waste from accumulating in corners



The dust-prevention plate helps reduce waste accumulation in corners.

POINT 5

Easy to clean



* Left-side bottom panel removed

The bottom panel is removable. The bottom panel can be removed for easy cleaning of the panel and the ground underneath.



● To prevent tipping, be sure to carry out the specified anchoring work. Failure to do so may result in collapse or damage. (Anchor bolts included.)

● Do not install in locations exposed to strong winds, such as rooftops or balconies, where safety cannot be ensured.